



# PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

## STYLE NL-630W

**DESCRIPTION:** Woven Nylon, Thermal Transfer, Fire Retardant

**SPECIFICATIONS:**

Base Denier: 70  
Total Weight:  $3.77 \pm 0.20$  oz./sq. yd.  
Thickness:  $0.0047 \pm 0.0005$  in.  
Tear Strength (MD):  $684 \pm 250$  grams  
Tear Strength (CD):  $1144 \pm 400$  grams

**GENERAL:** Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. This product has an extra smooth surface on one side for thermal transfer printing, and exhibits an exceptionally soft hand. This product meets requirements of FMVSS 302. This product does not contain halogen or antimony based fire retardants. This product is tested for compliance and individual lot certifications will be sent at time of shipment.

**Recommended Printing Methods:** Thermal Transfer, Flexography, Hot Stamping and Offset.

**ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM TRIAL MATERIAL. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS FINAL PRODUCT OR SHIPPING SPECIFICATIONS.**



Worthen Industries  
1125 41st Street SE  
Grand Rapids, MI 49508

Tel: (616) 742-8990  
Fax: (616) 742-8995  
[www.worthenindustries.com](http://www.worthenindustries.com)