



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE PS-317P

DESCRIPTION: Woven Polyester, Pearlescent

SPECIFICATIONS:

Base Denier: 70
Total Weight: 1.90 ± 0.20 oz./sq. yd.
Thickness: 0.0035 ± 0.0005 in.
Opacity: 85%
Stiffness (MD): 12 ± 10 mg
Stiffness (CD): 14 ± 10 mg
Tear Strength (MD): 355 ± 80 grams
Tear Strength (CD): 305 ± 50 grams

GENERAL: Coated with urethane on both sides and coated with a satin finish on one side. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges.

**Recommended
Printing Methods:** Flexography. Offset, Screen Printing and Hot Stamp

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com