



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE PS-370W

DESCRIPTION: Woven Polyester, dye resistant

SPECIFICATIONS:

Base Denier: 70
Total Weight: 2.40 ± 0.30 oz./sq. yd.
Thickness: 0.0037 ± 0.0005 in.
Opacity: >85%
Stiffness (MD): 12 ± 2 mg
Stiffness (CD): 9 ± 2 mg
Tear Strength (MD): 230 ± 80 grams
Tear Strength (CD): 350 ± 80 grams

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. PS370W exhibits an exceptionally soft hand. The product will remain stable at elevated temperatures of 320 to 340°F. At these elevated temperature conditions, the product will not curl, stiffen, or discolor significantly. PS370W is an ultra-durable label product, made to withstand harsh wash conditions with minimal print loss, and superior dye deposition resistance. PS370W also meets the requirements of Oeko-Tex Standard 100 for restricted chemicals.

**Recommended
Printing Methods:** Flexography. Offset and Hot Stamp

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com