



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE PS-606B

DESCRIPTION: Thermal Transfer, Black Woven Polyester

SPECIFICATIONS:

Base Denier: 70
Total Weight: 2.80 ± 0.30 oz./sq. yd.
Thickness: 0.0035 ± 0.0005 in.
Opacity: 99%
Stiffness (MD): 12 ± 2 mg
Stiffness (CD): 9 ± 2 mg
Tear Strength (MD): 230 ± 80 grams
Tear Strength (CD): 270 ± 80 grams

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. This product has an extra smooth surface on both sides for thermal transfer printing, and exhibits an exceptionally soft hand. The product will remain stable at elevated temperatures of 320 to 340°F for up to 20 min. At these elevated temperature conditions, the product will not curl, stiffen, or discolor significantly.

Recommended Printing Methods: Thermal Transfer, Flexography. Offset and Hot Stamp

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com