



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE RP-742W

DESCRIPTION: Nonwoven Spun-bonded Polyester

SPECIFICATIONS:

Total Weight: 3.50 ± 0.20 oz./sq. yd.
Total Thickness: 0.0090 ± 0.0010 in.
Opacity: >90%
Tear Strength (MD): 445 ± 100 grams
Tear Strength (CD): 670 ± 200 grams
Stiffness (MD): 105 ± 30 mg
Stiffness (CD): 70 ± 30 mg

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Exhibits excellent punching capabilities.

**Recommended
Printing Methods:** Flexography, Screen Printing, Hot Stamp, Dot Matrix

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com