



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE WB-550W

DESCRIPTION: Laser Printable Nonwoven Polyester/Cellulose Blend

SPECIFICATIONS:

Total Weight: 3.00 ± 0.20 oz./sq. yd.
Thickness: 0.0064 ± 0.0010 in.
Opacity: 90%
Stiffness (MD): 115 ± 20mg
Stiffness (CD): 118 ± 20mg
Tear Strength (MD): 80 grams (min)
Tear Strength (CD): 100 grams (min)

GENERAL: A non-woven cellulose/polyester blend designed for high speed laser print processing. Coated with acrylic on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements for commercial laundering and dry cleaning. Exhibits excellent punching capabilities. WB-550W is resistant to shrinking and curling, and degradation from rot, mildew and perspiration.

**Recommended
Printing Methods:** Laser, Flexography and Dot Matrix.

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com