



WORTHEN COATED FABRICS LABEL GROUP

PRODUCT SPECIFICATIONS



STYLE PB-276S

DESCRIPTION: Woven Satin Polyester

SPECIFICATIONS:

Total Weight: 4.70 ± 0.30 oz./sq. yd.
Thickness: 0.0070 ± 0.0005 in.

Stiffness (MD): 12 ± 2 mg
Stiffness (CD): 14 ± 2 mg

Tear Strength (MD): 1500 ± 300 grams
Tear Strength (CD): 1800 ± 300 grams

Opacity: 85%

GENERAL: PB-276S is a woven satin polyester manufactured specifically for conversion into high quality, permanent care labels, developed along guidelines proposed by the Consumer Products Division of the Federal Trade Commission. PB-276S demonstrates superior weave integrity, excellent smoothness of hand, and fair resistance against fadeout of imprinting from repeated commercial washings and dry cleanings. This non-fray acrylic-coated polyester also withstands noticeable discoloration or deterioration from exposure to commonly used permanent press dry cleaners. The product is highly resistant to shrinking or curling, and effectively resistant to degradation from rot, mildew, and perspiration.

Recommended

Printing Methods: Offset, Dot Matrix, Hot Stamping, and other impact-style print methods.

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com