



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE PK661W

DESCRIPTION: Thermal Transfer, Woven Polyester

SPECIFICATIONS:

Base Denier: 50/70
Total Weight: 2.40 ± 0.20 oz./sq. yd.
Thickness: 0.0037 ± 0.0005 in.
Opacity: 92%
Whiteness: Blue white shaded
Tear Strength (MD): 80 ± 10 grams
Tear Strength (CD): 136 ± 10 grams
Sheffield Smoothness: <50 maximum

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IIIA wash test requirements. Ravel proof edges. This product has an extra smooth surface on both sides for thermal transfer printing, and exhibits an exceptionally soft hand. The product will remain stable at elevated temperatures of 320 to 340°F for up to 20 min. At these elevated temperature conditions, the product will not curl, stiffen, or discolor significantly.

Recommended Printing Methods: Thermal Transfer, Flexography. Offset and Hot Stamp

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Printable Fabric Solutions
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com