



WORTHEN COATED FABRICS LABEL GROUP

## PRODUCT SPECIFICATIONS



### STYLE PS-650-1WNSN

**DESCRIPTION:** Woven Polyester, Heat Seal Coated

**SPECIFICATIONS:**

Base Denier: 70  
Total Weight: 5.55 ± 0.30 oz./sq. yd.  
Thickness: 0.0061 ± 0.0005 in.  
Stiffness MD: 44 ± 2 mg.  
CD: 44 ± 2 mg.  
Opacity: 85% minimum  
Tear Strength MD: 200 ± 20 gm.  
CD: 208 ± 20 gm.

**GENERAL:** Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. This product has an extra smooth surface on one side for thermal printing, and exhibits an exceptionally soft hand.

The heat seal adhesive is applied at 3 mils thickness. Recommended adhesive application conditions are a temperature of 350°F, under light pressure, for 3 seconds. The adhesive has excellent bond strength to cottons, poly/cottons, and polyester fabrics, and demonstrates excellent wash and dry cleaning resistance.

**This product meets AAFA and OEKE TEX 100 Standards for organotin content.**

**Recommended**

**Printing Methods:** Thermal Transfer, offset, flexography, and Hot Stamp.

**ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.**



Worthen Coated Fabrics Label Group  
Worthen Industries  
1125 41<sup>st</sup> Street SE  
Grand Rapids, MI 49508

Tel: (616) 742-8990  
Fax: (616) 742-8995  
[www.worthenindustries.com](http://www.worthenindustries.com)