



STYLE TD412W Tyvek

DESCRIPTION: HP Indigo printable Tyvek®, Printable 2 sides

SPECIFICATIONS:

Total Weight: 89 ± 5 g/m²
Thickness: 0.21 ± 0.02 mm (8.5 +/- 0.7 mils)
Opacity: 99%
Tear Strength (MD): 825 grams (min)
Tear Strength (CD): 655 grams (min)
Gurley Stiffness: 177 mg MD, 100 mg CD

GENERAL: TD-412W is an 8740D grade Tyvek® coated on both sides with a durable coating for improved HP Indigo printing. The coated surface enables superior toner adhesion and scratch resistance off-press, and imparts improved dimensional stability to the sheet for optimized duplex printing. The coating/toner interface is designed to be durable to a wide range of environmental conditions.

Recommended Printing Methods: HP Indigo, offset, flexography. **DO NOT USE THIS SHEET FOR ANY KIND OF DRY TONER HOT FUSING PRINT PROCESS**

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.

Fusion Digital Paper
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.fusiondigitalpaper.com